





<b>Head Type / Platform Type</b>	Thick Head / Knurled Platform
<b>Material</b>	Steel
<b>Finish</b>	Zinc Plate



H = Head Diameter  
T = Head Thickness  
L = Body Length

\*Dimensions in millimeters

Part Number	Thread Size	H max.	T max.	S max.	Hole Size (+0.13)	Sheet Thickness min.	Dist. C/L hole to edge min.	Hole in mating part max.	Tightening Torque(Nm) rec.					
TTTKCZ-040***	M4	6.16	1.00	2.20	4.00	0.8	8.0	5.0	3.5					
TTTKCZ-050***	M5	7.80	1.14	2.40	5.00	0.9	10.7	6.5	4.4					
TTTKCZ-060***	M6	9.40	1.27	2.80	6.00	1.0	11.5	7.5	10.0					
TTTKCZ-080***	M8	12.5	1.78	3.50	8.00	1.5	12.7	9.5	22.0					
TTTKCZ-080***	M10	15.7	2.30	6.20	10.00	2.3	13.7	11.5	37.0					
Thread Size	Available Lengths(L)													
M4	8	10	12	14	15	16	18	20	25	30				
M5	8	10	12	14	15	16	18	20	25	30				
M6		10	12	14	15	16	18	20	25	30	35	40	50	60
M8			12	14	15	16	18	20	25	30	35	40	50	60
M8				14	15	16	18	20	25	30	35	40	50	60