




Head Type	Dome Head
Material	A5052
Finish	Polished



*Dimensions in millimeters

Part Number	Rivet Diameter (D) nom.	Hole Size	Body Length(L) max.	Grip Range	Head Diameter (H) max.	Head Thickness (T) max.	Standard Strength (kN) typ.	
							Shear	Tensile
SHRDAP-024032	2.4	2.49~2.55	3.2	0.00~1.50	4.2	0.9	0.30	
SHRDAP-024048			4.8	1.60~3.10				
SHRDAP-024064			6.4	3.10~4.70				
SHRDAP-024079			7.9	4.80~6.30				
SHRDAP-024095			9.5	6.30~7.90				
SHRDAP-024111			11.1	8.00~9.50				
SHRDAP-032032	3.2	3.28~3.34	3.2	0.00~1.50	5.5	1.2	0.60	
SHRDAP-032048			4.8	1.60~3.10				
SHRDAP-032064			6.4	3.10~4.70				
SHRDAP-032079			7.9	4.80~6.30				
SHRDAP-032095			9.5	6.30~7.90				
SHRDAP-032111			11.1	8.00~9.50				
SHRDAP-040048	4.0	4.09~4.16	4.8	1.60~3.10	6.5	1.5	1.00	
SHRDAP-040064			6.4	3.10~4.70				
SHRDAP-040079			7.9	4.80~6.30				
SHRDAP-040095			9.5	6.30~7.90				
SHRDAP-040111			11.1	8.00~9.50				
SHRDAP-040125			12.5	9.50~11.0				
SHRDAP-048056	4.8	4.85~4.93	5.6	1.60~3.10	8.9	1.8	1.50	
SHRDAP-048072			7.2	3.10~4.70				
SHRDAP-048088			8.8	4.80~6.30				
SHRDAP-048103			10.3	6.30~7.90				
SHRDAP-048119			11.9	8.00~9.50				
SHRDAP-048135			13.5	9.50~11.0				